about 3,000 workers, 40 percent of whom were women. Work was done in 3 shifts. Theselages of jet airraft, possibly MG-15s, were manifectured at the plant. The morthly output was estimated at 140 fuestinges. In early September 1953, employees of the plant believed that the work force was to be reduced. This assumption was supported by the fact that some workers could terminate their work contract without difficulties although en intense recruiting campaign for the Choch mirreft industry had been conducted in 1953. The curting department of the aircraft plant employed a total of about 60 workers working 3 shifts. The foremen of the decortment was Jan Vik the 2 clustric bend saws for the cutting of steel, 1 clicular saw for the cutting of breaking. I machine, and 5 small boring matchines. Note of the haterial machined in the department was buralumin. Sheet metal seculous were also processed there, however. Of the larger fuselage sections, series of LAD units were generally produced. Other departments boated at the plant included the hardening department, the sheet-nextl department, the assembly shop, the sheet-nextl cutting department, and the anodic breatment department. Work in the hardening department, the sheet-nextled department was done in 2 shifts with 5 to 10 workers ussigned to each shift. The metal was hardened at a temperature of about 500°C in 2 baths filled with a liquid of undate-mined camposition. Work at the whest-matal department was done in 3 shifts. At the assembly shop, the ness out over sensenbled with the help of about 12 erecting scaffolds. Work was done in 3 shifts at this department. Each workpiese was accumpanted by a work sheet on its way through the different department of the plant. On these sork sheets it was stated that the Duralumin treated had a strength of 35 kg per square ma. CLASSICANION CORFIDENTIAL - U.S. OFFICIALS ONLY	COUNTRY Caschoslovakia DATE DISTR 2 September 1954 SUBJECT Vysochry Plant, Aero National Enterprise, Prague—No. OF PAGES 2 25X1 PLACE Mysochry Plant, Aero National Enterprise, Prague—No. OF PAGES 2 SUPPLEMENT TO SUPPLEMENT TO REPORT NO. 25X1 SUPPLEMENT TO REPORT NO. 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMATION The supplement of the supplement of whose were uncasen. Nork was fone in 3 shifts. The supplement of	A	Approved For Release 2007/08 CLASSIFICATION CONTROL	8/29 : CIA-RDP80-0081 ラブザかり、デ せょう。 0デブ	0A004700080006-9 CLAIG COLY	entre de la companya
COUNTRY Csechos ownkis Differences Program-No. OF PAGES 2 25X1 Vysockny Pient, Aero National Enterprise, Program-No. OF PAGES 2 25X1 PAGE NO. OF FROMES 2 25X1 NO. OF FROMES 3 25X1 25X1 THIS IS UNEVALUATED INFORMATION 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMATION The southly owner was a second of them was stored. We was fone in 3 skitts. The southly owner was not believed that the work force was to be reduced. This assumptions of the pient believed that the work force was to be reduced. This assumptions of the pient believed that the work force was to be reduced. This assumptions of the pient believed that the work force was to be reduced. This assumption was not difficulties although an intense recruiting comparing for the Cook intense in Stiff Cook in the Cook was to be reduced. This assumption was difficultied although an intense recruiting comparing for the Cook intense in the cook was a supported by the fact that ones workers ould teardinate their work workers of the pient difficulties although a supported to the continue of the correction was a supported by the fact that ones workers ould teardinate their workers workers ould teardine to their work workers ould teardine to their work working of the pient of the correction was a supported by the fact that ones workers ould tearding department was continued to the continue of the correction was all will reduced. The correction was all will reduced at this general and the continue of the correction was a supported by the correction was and an improved there, however, of the larger fuency, sorting marrians, but of the execution of the correction was adverted and there is no workers of the plant. Shows done in 3 shifts at the assembly chop, the ness and rear sections of the free larger to make hardened at the supertensor of the plant was done in 3 shifts at the assembly chop, the ness and r	COUNTRY Casches. Ovakin Date National Enterprise, Prague-HO OF PAGES 2 25X1 PLACE **NO. OF ENCIS.** **OFFICE OF SUPPLEMENT TO REPORT NO.** **PRESENT AND A COUNTRY NATIONAL PROPERTY OF THE PROPERTY OF T	W mry ?	The same of the sa	File and the second of the sec	REPORT	
SUBJECT Vysocomy Final, Aero National Enterprise, Prague-HO. OF PAGES 2 25X1 PAGE ACQUIRED DATE OF NIPO. SUPPLEMENT TO REPORT NO. 25X1 THIS IS UNEVALUATED INFORMATION The activity output was contained at Mio face insuring the reduced. This assisting does was proported by the facet that some vorticers could teachine 1955, applicable of the plant the world force was to be reduced. This assisting department believed that the world force was to be reduced. This assisting department information the accordance of the plant the world force was to be reduced. This assisting department information information to be accordance of the plant the world force was to be reduced. This assisting department information to be accordance of the plant the some vorticers could teaching the reduced. This assisting department was accordance of the plant accordance of the plant included the face mental was accordance as the plant included there, however, of the larger fuselings sections and the accordance of the plant included there, however to the larger fuselings sections of the fuselings of the plant the insulance of the plant is a small accordance of the plant included the hordering department, was admitted in the section of the plant included the plant included in the section of the plant included in the section of the plant included in the plant included in the plant included in the plant included in the plant included included in the plant i	SUBJECT Vysocary Flant, Aero National Enterprise, Prague-NO. OF PAGES 2 PLACE ACQUIRED DATE OF NIFO. THIS IS UNEVALUATED INFORMATION 25X1 THIS IS UNEVALUATED INFORMATION 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMATION 25X1 THIS IS UNEVALUATED INFORMATION 35 Supplement 1959, the precipity of the plant unit of the plant information in 3 shifts. 25X1 THIS IS UNEVALUATED INFORMATION 35X1 THIS IS UNEVALUATED INFORMATION 55X1 THIS IS UNEVALUATED INFO	ing mga ag Tidan sa ang agagagagagagagagagagagagagagagagag	INFORMATIO	N REPORT	CD NO.	25X16 * *
FLACE ACQUIRED DAIE OF INFO. THIS IS UNEVALUATED INFORMATION 25X1 THIS IS UNEVALUATED INFORMATION 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INF	PLACE ACQUIRED DATE OF INFO. 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMATION This is unevaluated in the second of th	COUNTRY	Czechos ovakia	(1995년 - 1995년 - 1995 - 1995년 - 1995	DATE DISTR 2	September 1954
ACQUIRED DATE OF SUPPLEMENT TO REPORT NO. 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUA	EME OF SUPPLEMENT TO REPORT NO. 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMA	SUBJECT		Enterprise, Prague	-NO. OF PAGES	
SUPPLEMENT TO REPORT NO. 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED INFORMATION THE ACCOUNTY OF THE ACCOUNTY	NFO. NFO. SUPPLEMENT TO REPORT NO. 25X1 THIS IS UNEVALUATED INFORMATION THIS IS UNEVALUATED IN				NO. OF ENCLS.	*
This is unevaluated by the fact that the work force was to be reduced. This sawang does not exclude a shifts. The forces of the fact that she was a quipped with switch of the hardraft shifts. The forces of the department was quipped with a shifts. The forces of the natural than shifts and the shifts. The forces of the fact that she perturb the southers are forced by the fact that she perturb work against the shifts. The forces of the fact that she work force was to be reduced. This sawang don was supported by the fact that some workers could terrinate wheir work southers at those of the fact that some workers could terrinate wheir work southers at those of the fact that some workers could terrinate wheir work southers at those of the fact that some workers could terrinate wheir work southers at those of the according to the same workers work to be reduced. This sawang don was supported by the fact that some workers could terrinate wheir work southers at those of the fact that some workers could terrinate wheir work southers at those of the fact that some workers are the fact that some workers worked that the work force was to be reduced. This sawang don was supported by the fact that some workers worked the saw for the fact that some workers worked the saw for the cutting of stream was aquipped with a shorter bend was to the natural transfer of the natural produced. Other departments located at the plant included the hardwains department, the same was a provided at a beaperature of about 500°C in 2 baths filled with a liquid of wasterness. Work in whe hardwains department, and the another treatment department. Work in whe hardwains department was done in 3 shifts. It was essently shop, the none and rear sections of the fuselages were assembled with the help of about 50°C in 2 baths filled with a liquid of wasterness and the work from the hardwains department. As done in 3 shifts, it was assembly shop, the none and rear sections of the fuselages were assembled with the help of about 50°C in 2 baths filled with	THIS IS UNEVALUATED INFORMATION This is unevaluated information and angular a					638119
THIS IS UNEVALUATED INFORMATION The activation to external to a manner access to the control of	THIS IS UNEVALUATED INFORMATION The correction to a case of the following the control of the country of the co				·	25X1
about 5,000 workers, 40 percent of whom were unman. Work was done in 3 shifts. Tueslages of jot aircraft, possibly MG-15s, were manufactured at the plant. The moithly output was estimated at L40 fursinges. In early September 1953, employees of the plant believed that the work force was to be reduced. This assumption was supported by the fact that some workers could terriant their work contract without difficulties although en intense recruiting compaign for the Good mirroraft industry had been conducted in 1953. The sunting department of the aircraft plant employed a total of about 60 workers working 3 shifts. The foremen of the department was equipped with 2 shorten bend ways for the cutting of steal, 1 chicular say for the cutting of Devaluatin. Short 7 vertical militing machines, and 5 small boring machines. Nort of the material machined in the department was Duralumin. Shert metal necrooms were also processed there, however. Of the larger fuselage sections, series of L40 units were generally produced. Other departments located at the plant included the hardening department, the sheet-nextl department was done in 2 shifts with 5 to 10 workers assigned to each shift. The metal was hardened at a temperature of about 500° C in 2 baths filled with a liquid of undetermined composition. Work at the sheet-nextl department was done in 3 shifts. At the assembly shop, the ness out ears sections of the fuselages were assembled with the help of about 12 erecting scaffolds. Work was done in 3 shifts at this department. Each workeless as accumpanied by a work sheets it was stated that the Duralumin treated had a strength of 35 kg per square ma. The material-testing department of the plant was in a small factory on Machines at the aircraft plant proper. Work was done in 2 mass operations are strength of 25 kg per square ma. CLASSECATION COMMITTEE DEPARTMENT U.S. CEFFICIALS CRAPT	About 1,000 workers, 40 percent of whom were ucmen, Work was done in 3 shifts. Tuestages of jet aircraft, possibly MiG-15s, were manufactured at the plant. The monthly output was estimated at 140 fuesiages. In early September 1953, employees of the plant believed that the work force was to be reduced. This assumption was supported by the fact that some workers could terrinate wheir work contract without difficulties although an intense recruiting compaign for the Casch aircraft industry had been conducted in 1953. The conting department of the aircraft plant employed a total of about 60 workers working 3 shifts. The forcemen of the department was equipped with 2 electric bend have for the cutting of steel, 1 cheular saw for the cutting of Steel, and 5 small boring machines. Next of the material machined in the department was small boring machines. Next of the material machined in the department was small services also processed there, however. Of the larger fuselage sections, series of 120 cutts were generally produced. Other departments bosated at the plant included the hardening department, the sheet-weald department, the assembly shop, the sheet-weald cutting department, and the anodic treatment department. Work in the hardening department was done in 2 shifts with 5 to 10 verkers assigned to each shift. The metal was hardened at a temperature of about 500° G in 2 baths filled with a liquid of undetermined camposition. Work at the sheet-metal department was done in 3 shifts at this department. Bach workplace was accumpanied by a work sheet on its way through the different departments of the plant. On these work sheets it was stated that the Duralumin treated had a strength of 35 kg, per square non. The material-desting department of the plant was in a small factory on the Casa of through opposite the aircraft plant proper. Work was done in 2	OF THE UNITED ST. TES, T	THRUIN THE MEANING OF TITLE 18, SECTIONS 723	THIS IS UNEVAL	UATED INFORMATIO	N
workers working 3 shifts. The foreman of the decortment was Jan Vik The department was equipped with 2 electric band ways for the cutting of steel, 1 choular saw for the cutting of Duralunds. about 7 vertical militing machines, and 5 small boring machines. Next of the material machined in the department was Duralumin. Sheet metal sections were also processed there, however. Of the larger fuselage sections, series of LAD units were generally produced. Other departments homesed at the plant included the hardening department, the sheet-nexts department, the assembly shop, the sheet-nexts cutting department, and the anodic treatment department. Work in the hardening department was done in 2 shifts with 8 to 10 workers assigned to each shift. The metal was hardened at a temperature of about 500° C in 2 baths filled with a liquid of undsteamined composition. Work at the sheet-metal department was done in 3 shifts. At the assembly shop, the nose and rear sections of the fuselages were assembled with the help of about 12 energing scaffolds. Fork was done in 3 shifts at this department. Each workplace was accumpanied by a work sheet on its way through the different departments of the plant. On these work sheets it was stated that the Duralumin treated had a strength of 35 kg per square ma. The majorial-desting department of the plant was in a small factory on Me locals different department. For work was done in 2 CLASSIFICATION CONFIDENTIAL - U.S. CFFICIONS ONLY CLASSIFICATION CONFIDENTIAL - U.S. CFFICIONS ONLY	workers working 3 shifts. The foreman of the decertment was Jan VIk The department was equipped with 2 electric bend saws for the cutting of steel, 1 choular saw for the cutting of Duralumin, about 7 vertical milling machine, and 5 small boring machines. Nost of the material machined in the department was Duralumin. Sheet metal sections were also processed there, however. Of the larger fuselage sections, series of had units were generally produced. Other departments because at the plant included the hardening department, the sheet-netal department, the assembly shop, the sheet-netal cutting department, and the anothe treatment department. Work in the hardening department was done in 2 shifts with 8 to 10 workers assigned to each shift. The metal was hardened at a temperature of about 500° G in 2 baths filled with a liquid of undstermined composition. Nork at the obset-netal department was done in 3 shifts. At the assembly shop, the nose and rear sections of the fuselages were assembled with the help of about 12 eventing scaffolds. Nork was done in 3 shifts at this department. Each workplace was accumpanied by a work sheet on its way through the different departments of the plant. On these sork sheets it was stated that the Duralumin treated had a strength of 35 kg per square ma. The material-vesting department of the plant was in a small factory on Ma Grane Stronge opposite the aircraft plant proper. Work was done in 2	about 3,00 Puselances The monthlenphoyees assumption work conta	00 workers, 40 percent of whom of jet aircraft, possibly MiG- by output was estimated at 140 of the plant believed that the usual supported by the fact the ract without difficulties although the second supported by the fact the ract without difficulties although the second supported by the fact the ract without difficulties although the second supported by the fact the ract without difficulties although the second support of the second	vere ucmen. Work wa 15s, vers manufactu fussinges. In early work force was to it some workers ecul- ngh an intense recr	s done in 3 shift red at the plant. Saptember 1953, be reduced. This d terrinate cheir	25X1
sheet-metal department, the assembly shop, the sheet-metal cutting department, and the anodae treatment department. Work in the hardening department was done in 2 shifts with 8 to 10 workers assigned to each shift. The metal was hardened at a temperature of about 500° C in 2 baths filled with a liquid of undetermined composition. Work at the abest-metal department was done in 3 shifts. At the assembly shop, the nose and rear sections of the fuselages were assembled with the help of about 12 eventing scaffolds. Work was done in 3 shifts at this department. Each workplead was accompanied by a work sheet on its way through the different departments of the plant. On these work sheets it was stated that the Duralumin treated had a strength of 35 kg. per square mm. The material testing department of the plant was in a small factory on Ma Charles Stream opposite the aircraft plant proper. Work was done in 2	sheet-metal department, the assembly shop, the sheet-metal cutting department, and the anodic treatment department. Work in the hardening department was done in 2 shifts with 5 to 10 workers assigned to each shift. The metal was hardened at a temperature of about 500°C in 2 baths filled with a liquid of undetermined composition. Work at the absentmental department was done in 3 shifts. At the assembly shop, the nose and rear sections of the fuselages were assembled with the help of about 12 erecting scaffolds. Work was done in 3 shifts at this department. Each workplace was accompanied by a work sheet on its way through the different departments of the plant. On these work sheets it was stated that the Duralumin treated had a strength of 35 kg per square ma. The material-testing department of the plant was in a small factory on Ma Caras Streams opposite the aircraft plant proper. Work was done in 2	workers we with 2 elecuting of machines.	patric bend saws for the cutting Duralumin, about 7 vertical blost of the material machined mions were also processed there	the department was The depart g of steel, 1 circul militing machines, s in the department was , however. Of the 1s	Jan Vlk ment was equipped lar sav for the ant 5 small borin as Durelumin. S	g hees
CLASSIFICATION CONFIDENTIAL - U.S. OFFICIALS CHAPTER TO A STREET ON THE PROPERTY OF THE PROPER	Caras Strouss opposite the aircraft plant proper. Nork was done in 2	aheat-asta and the an dons in 2 hardened a undetermin 3 shifts. were assem in 3 shift sheet on i	il department, the assembly sho notic treatment department. Wor shifts with S to 10 workers as it a temperature of about 500° ned composition. Work at the sh At the assembly shop, the nose abled with the help of about 12 is at this department. Each wor its way through the different d is it was stated that the Dural	p, the sheet-mewal of k in the hardening of signed to each shift of in 2 baths filled est-metal department and rear sections of eresting scaffolds, kplece was accompanie courtments of the pleartments of the pleartments.	cutting department was t. The metal was with a liquid of t was done in of the fuselages. Vork was done led by a work lant. On these	t ,
CLASSIFICATION CONFIDENTIAL - U.S. OFFICIALS CNLV		. The materi	Al-testing department of the p	lant was in a small t proper. Work was d	factory on Me	
1 VOZ 121 VAN W NSRB DISTRIBUTION			, , , , , , , , , , , , , , , , , , ,	The second secon		
CLOS 152 MAY 19 NSRB DISTRIBUTION						
SOUTH COMMENT OF THE PROPERTY		. (1) (2) [40]			DIXE CMAY	CONTROL MANAGE AND AND THE CO. TO.
26 My 161 W My F7!	ANN TENS MALEN DISTRICTION	MN TE	· · · · · · · · · · · · · · · · · · ·			25)

Approved For Release 2007/08/29: CIA-RDP80-00810A004700080006-9

CONT	tden(tal/contr o l -	. 18,8. officials of	NLY	
•	. 2 .			
				25 X 1
tensile strength of entire fuselag that the departme inferred from the	of individual sec es was tested at a nt also worked for fact that vings	y one shift was em tions of fuselages this department. I r other eircraft p of small eircraft yoosaxy Plant of Ac	and also t appeared lants. This was	25 X 1
		9 (* 14.44)		• •
				25 X 1
			·.	
		r		<u>;</u>

CONSIDENTIAL/CONTROL - U.S. OFFICIALS ONLY